

Welmon Woodplast Pvt Ltd is one of the dominant manufacturers and exporter of plastic corrugated sheet form Morbi, India. Our Product Range are PP Corrugated Sheet, PP Flute Board, H-Line PP Hollow Sheet, S-Line PP Hollow Sheet, Sunpack Sheet, Floor Protection Sheet, Corrugated Layer Pad, Corflute, Coroplast, Correx, Corrugated Hollow Flute etc.

Specification Table:

Thickness	GSM	Color	Size
3MM	500	White	1220mm x 2440mm
4MM	600	White	1220mm x 2440mm
5MM	700	White	1220mm x 2440mm
6MM	850	White	1220mm x 2440mm

Tolerances:

Dimensional tolerance across the flutes or width +/- 2mm
Dimensional tolerance along the flutes or length +/- 20mm

Characteristics:

Softening temperature (BS2782: 102D ISO 1306)	85 Deg. C
Crystalline melting point	160-175 Deg. C
Flash ignition temperature c	a 350 Deg. C
Self ignition temperature	ca 380 Deg.C
Calorific value	11000 Cal.Kg
Specific heat	0.46 Cal./gm Deg. C
Limiting oxygen index (ASTM D 2863)	0.174-0.180
Burn rate (FMVSS 302)	5.3-8.2 cm/min

